

TRENTON®

Corporate Office:
The Trenton Corporation
7700 Jackson Rd.
Ann Arbor, MI 48103
734/424-3600
Fax: 734/426-5882

Houston Div./Export Office:
1880 S. Dairy Ashford Rd.
Suite 697
Houston, TX 77077
281/556-1000
Fax: 281/556-1122

Fill-Coat #6®



Description:

Fill-Coat #6 is a cold-installed/high temperature petroleum-based casing filler compound that can be installed at ambient temperatures as low as 50°F (10°C) with portable pumps. The product is used in bridge abutment casings, and it can be used in casings with elevated temperatures.

End Use:

Fill-Coat #6 is used to fill the annulus of gas distribution bridge abutment casings. It prevents corrosion by filling the void in the casing annulus. In addition, new water is prevented from entering the wax-filled casing. Applications include above-ground cased pipe (like bridge abutment casings).

Application Procedures:

Fill-Coat #6 can be installed by a variety of portable air-powered mastic pumps (1, 5, or 50 gallon capacity). The material is pumped into the annulus of the casing until the casing is full. The casing ends can be sealed with Trenton Fill-Putty, Trenton #2 Wax-Tape, or an epoxy filler once it is full.

Packaging:

50-gallon drums

Properties:

Nonmelting
Heavier than water
Anticorrosive
Water resistant
Dielectric
Inert
Nontoxic
Nonflammable
Pliable

Technical Specifications:

Flash Point, ASTM D92 greater than 300°F
Specific Gravity 1.02 to 1.08
Temperature Range 30°F to 225°F
Color dark brown
Consistency grease-like
Dielectric Strength greater than 100
volts per mil
Density, ASTM D1475 7.898 lbs. per gallon